



# HOS BLACK FOOT

HOSMAX310 Offshore Supply Vessel



## DIMENSIONS AND REGULATORY INFORMATION

<b>Length:</b>	302 ft 0 in (92.0 m)	<b>Beam:</b>	64 ft 0 in (19.5 m)	<b>Draft Max:</b>	21 ft 1 in (6.43 m)
<b>Gross:</b>	4,217 GT	<b>Net:</b>	1,265 NT	<b>Draft Min:</b>	11 ft 3 in (3.43 m)
<b>IMO:</b>	9647693	<b>O.N.:</b>	1244582	<b>Flag:</b>	U.S.
<b>Certifications:</b>	Oceans-SOLAS, USCG Subchapter I, USCG Subchapter L				
<b>Classifications:</b>	Loadline, American Bureau of Shipping, +DPS-2, FFV-1, (E), +A1, +ACCU, +AMS, OSV, ENVIRO, GP, UWILD, ACP, CRC, OSR-C2				

## PERFORMANCE

<b>Cruise Speed:</b>	10.0 kts	133 gal/hr (503 l/hr)	<b>Max Speed:</b>	12.0 kts	208 gal/hr (787 l/hr)
----------------------	----------	-----------------------	-------------------	----------	-----------------------

## PROPULSION, MACHINERY AND STEERING

<b>Main Engines:</b>	4 x Caterpillar 3516C	<b>Total Rating:</b>	7,300 kW
		<b>Propeller Diameter:</b>	106 in (2,692 mm)
<b>Bow Thruster:</b>	2 x Schottel FPP Tunnel	<b>Total Rating:</b>	3,160 hp
<b>Main Propulsion :</b>	2 x Schottel Azimuthing Z-Drives	<b>Total Rating:</b>	6,700 hp
		<b>Power Generation:</b>	690V/60/3 phase

## CAPACITIES AND DELIVERY RATES

<b>Deadweight:</b>	6,055 LT (6,152 MT)	<b>Deck Area:</b>	202 ft x 55 ft (11,137 ft <sup>2</sup> ) 61.7 m x 16.8 m (1,034.6 m <sup>2</sup> )
<b>Deck Cargo:</b>	3,700 LT (3,759 MT)	<b>Deck Load Rating:</b>	1,024 lbs/ft <sup>2</sup> (5 MT/m <sup>2</sup> )
<b>Dry Bulk:</b>	14,350 ft <sup>3</sup> (406 m <sup>3</sup> )	<b>System Pressure:</b>	80 psi (5.5 bar)
<b>Liquid Mud:</b>	21,417 bbl (3,405 m <sup>3</sup> )	<b>Discharge Rate:</b>	1,000 GPM (227 m <sup>3</sup> /hr)
<b>Methanol:</b>	2,212 bbl (352 m <sup>3</sup> )	<b>Discharge Rate:</b>	250 GPM (57 m <sup>3</sup> /hr)
<b>Potable Water:</b>	62,549 gal (237 m <sup>3</sup> )		
<b>Recovered Oil (&lt;60 deg C FP):</b>	2,212 bbl (352 m <sup>3</sup> )		
<b>Recovered Oil (&gt;60 deg C FP):</b>	21,417 bbl (3,405 m <sup>3</sup> )		
<b>Rig Fuel:</b>	268,284 gal (1,015 m <sup>3</sup> )	<b>Discharge Rate:</b>	750 GPM (170 m <sup>3</sup> /hr)
<b>Rig Water:</b>	528,274 gal (2,000 m <sup>3</sup> )	<b>Discharge Rate:</b>	750 GPM (170 m <sup>3</sup> /hr)
<b>Cooler Area:</b>	600 ft <sup>3</sup> (17 m <sup>3</sup> )	<b>Freezer Area:</b>	400 ft <sup>3</sup> (11 m <sup>3</sup> )
<b>Off-ship Firefighting Monitors:</b>	2	<b>Total Flow Rate:</b>	10,586 gal/min (2,406 m <sup>3</sup> /hr)

## ELECTRONICS

AIS, Anemometer, Auto Pilot, CCTV Cameras, Cyscan, Depth Sounder, DGPS w/ AIS, DSDL, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, Radascan, S-band Radar, SARTs, Speed Log, SSAS, VHF Radio, VHF Radio (Handheld), VSAT, X-band Radar, VERIPOS

## ACCOMMODATIONS

17 air conditioned/heated staterooms certified for 50 person berthing.

## SPECIAL FEATURES

<b>Deck Crane:</b>	1 x Appleton EB70-53-33	<b>Max Lift @ Max Radius:</b>	3 MT @ 53 ft
		<b>Max Lift @ Min Radius:</b>	13 MT @ 16 ft
		<b>Personnel Rating:</b>	0.6 MT
<b>Watermaker Cap.:</b>	2,000 USG/day		

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.