




Service with Energy

HOS RUGER

HOSMAX280 Offshore Supply Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	280 ft 0 in (85.3 m)	Beam:	60 ft 0 in (18.3 m)	Draft Max:	19 ft 3 in (5.87 m)
Gross:	2,996 GT	Net:	1,066 NT	Draft Min:	10 ft 3 in (3.12 m)
IMO:	9385269	O.N.:	1193951	Flag:	U.S.
Certifications:	Oceans-SOLAS, USCG Subchapter I, USCG Subchapter L				
Classifications:	Loadline, American Bureau of Shipping, +DPS-2, (E), +A1, +AMS, +ACC, ACP, OSR-C2				

PERFORMANCE

Cruise Speed:	10.0 kts 145 gal/hr (549 l/hr)	Max Speed:	12.7 kts 290 gal/hr (1,098 l/hr)
----------------------	-----------------------------------	-------------------	-------------------------------------

PROPULSION, MACHINERY AND STEERING

Main Engines:	2 x Caterpillar 3608	Total Horsepower:	6,598 bhp
Propellers:	CPP, High Efficiency, 4-Blade	Propeller Diameter:	106 in (2,692 mm)
Primary Generators:	2 x Caterpillar 3508B	Total Rating:	1,820 kW
Shaft Generators:	2 x Kato	Total Rating:	4,000 kW
Aft Bow Thruster:	1 x Rolls Royce CPP Swing Up Azimuth	Total Rating:	1,100 hp
Fwd Bow Thruster:	1 x Schottel CPP Tunnel	Total Rating:	1,700 hp
Stern Thruster:	1 x Schottel CPP Tunnel	Total Rating:	1,700 hp
Rudder:	High Lift, Independent Steering	Power Generation:	480V/60 Hz/3-Phase

CAPACITIES AND DELIVERY RATES

Deadweight:	4,738 LT (4,814 MT)	Deck Area:	201 ft x 50 ft (10,151 ft ²) 61.3 m x 15.4 m (943.0 m ²)
Deck Cargo:	2,450 LT (2,489 MT)	Deck Load Rating:	1,200 lbs/ft ² (6 MT/m ²)
Dry Bulk:	12,000 ft ³ (340 m ³)	System Pressure:	80 psi (5.5 bar)
Liquid Mud:	15,415 bbl (2,451 m ³)	Discharge Rate:	1,100 GPM (250 m ³ /hr)
Potable Water:	34,820 gal (132 m ³)	Discharge Rate:	1,400 GPM (318 m ³ /hr)
Rig Fuel:	326,454 gal (1,236 m ³)	Discharge Rate:	1,400 GPM (318 m ³ /hr)
Rig Water:	197,106 gal (746 m ³)	Freezer Area:	525 ft ³ (15 m ³)
Cooler Area:	560 ft ³ (16 m ³)		

ELECTRONICS

AIS, Auto Pilot, C-Nav, CCTV Cameras, Cyscan, Depth Sounder, DGPS w/ AIS, DSDL, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, Radascan, S-band Radar, SARTs, Speed Log, SSAS, VHF Radio, VHF Radio (Handheld), VSAT, Windbird, X-band Radar

ACCOMMODATIONS

12 air conditioned/heated staterooms certified for 29 person berthing.

SPECIAL FEATURES

Oil Spill Recovery:	ABS Capability Class 2	Recovered Oil Capacity:	15,415 bbl (2,451 m ³) (>60 °C FP)
Deck Crane:	1 x North Pacific MCF-530	Max Lift @ Max Radius:	1.4 MT @ 30 ft
Roll Damping:	Passive, Anti-Roll Tank	Deck Tuggers:	2 x 7 MT

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.