



# HOS RUNNING BUCK

HOSMAX280E Offshore Supply Vessel



## DIMENSIONS AND REGULATORY INFORMATION

<b>Length:</b>	286 ft 0 in (87.2 m)	<b>Beam:</b>	60 ft 0 in (18.3 m)	<b>Draft Max:</b>	19 ft 4 in (5.89 m)
<b>Gross:</b>	3,446 GT	<b>Net:</b>	1,463 NT	<b>Draft Min:</b>	11 ft 3 in (3.43 m)
<b>IMO:</b>	9645633	<b>O.N.:</b>	1323242	<b>Flag:</b>	U.S.
<b>Certifications:</b>	Oceans-SOLAS, USCG Subchapter I, USCG Subchapter L				
<b>Classifications:</b>	Loadline, American Bureau of Shipping, +DPS-2, FFV-1, (E), +A1, +ACCU, +AMS, OSV, ENVIRO, GP, ACP				

## PERFORMANCE

<b>Cruise Speed:</b>	10.0 kts	140 gal/hr (530 l/hr)	<b>Max Speed:</b>	13.5 kts	205 gal/hr (776 l/hr)
----------------------	----------	-----------------------	-------------------	----------	-----------------------

## PROPULSION, MACHINERY AND STEERING

<b>Main Engines:</b>	4 x Cummins QSK60DM	<b>Total Rating:</b>	7,300 kW
<b>Main Propulsion:</b>	2 x Schottel Azimuthing Z-Drives	<b>Total Rating:</b>	6,700 hp
<b>Bow Thruster:</b>	2 x Schottel FPP Tunnel	<b>Total Rating:</b>	3,160 hp
		<b>Power Generation:</b>	690V/60 Hz/3-Phase

## CAPACITIES AND DELIVERY RATES

<b>Deadweight:</b>	4,279 LT (4,347 MT)	<b>Deck Area:</b>	184 ft x 52 ft (9,568 ft <sup>2</sup> ) 56.1 m x 15.8 m (888.9 m <sup>2</sup> )
<b>Deck Cargo:</b>	2,657 LT (2,700 MT)	<b>Deck Load Rating:</b>	1,024 lbs/ft <sup>2</sup> (5 MT/m <sup>2</sup> )
<b>Dry Bulk:</b>	8,631 ft <sup>3</sup> (244 m <sup>3</sup> )	<b>System Pressure:</b>	80 psi (5.5 bar)
<b>Potable Water:</b>	25,439 gal (96 m <sup>3</sup> )	<b>Discharge Rate:</b>	750 GPM (170 m <sup>3</sup> /hr)
<b>Rig Fuel:</b>	948,906 gal (3,592 m <sup>3</sup> )	<b>Discharge Rate:</b>	260 GPM (59 m <sup>3</sup> /hr)
<b>Rig Water:</b>	442,541 gal (1,675 m <sup>3</sup> )	<b>Freezer Area:</b>	240 ft <sup>3</sup> (7 m <sup>3</sup> )
<b>Cooler Area:</b>	240 ft <sup>3</sup> (7 m <sup>3</sup> )		

## ELECTRONICS

AIS, Anemometer, Auto Pilot, CCTV Cameras, Cyscan, Depth Sounder, DGPS w/ AIS, DSDL, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, Radascan, S-band Radar, SARTs, Speed Log, SSAS, VHF Radio, VHF Radio (Handheld), VSAT, X-band Radar

## ACCOMMODATIONS

12 air conditioned/heated staterooms certified for 29 person berthing.

## SPECIAL FEATURES

<b>Off-ship Firefighting:</b>	FIFI I	<b>Number of Fire Monitors:</b>	2
<b>Watermaker Cap.:</b>	2,000 USG/day	<b>Total Flow Rate:</b>	10,568 gal/min (2,402 m <sup>3</sup> /hr)

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.